

New performances, new heights

THE 5800 SERIES

A COMMON SOLUTION FOR A WIDE VARIETY OF APPLICATIONS

The 5800 series of Pentair Fleck valves provide a common solution for a wide variety of filtration and softening applications. Developed on the same platform as the 5800, the 5810 and 5812 valves offer flexibility with a familiar appearance, while reducing carrying costs.

5800 5810 5812 MAXIMUM FLOW RATES M³/H (GPM)

	DF / UF	DF / UF / FILTER	DF / UF / FILTER
SERVICE ($\Delta p = 1 \text{ bar}$)	4.7 (21)	8.17 (36) / 7.9 (39) / 7 (31)	9.9 (43) / 8.9 (39) / 8.4 (37)
PEAK ($\Delta p = 1.8 \text{ bar}$)	6.1 (27)	10.6 (47) 10.1 (45) 9.0 (40)	12.7 (56) 11.9 (51) 10.7 (47)
KV (m³/hr).bar	4.7	8.1 / 7.7 / 7.8	9.7 / 8.7 / 8.1
BAKCKWASH (Δp = 1.7 ba	r) 3.9 (17)	6.3 (28) / 6.9 (30) / 7.5 (33)	7.5 (33) / 8.1 (36) / 9.9 (45)

2.5 INCH BASE

A GREAT TRADITION

The Pentair Fleck 5800 family sets a brand new standard for adaptability and innovative features. At the same time, they come from a company known for decades of expertise in the water industry, millions of units in service, and a tradition of rock solid reliability.

This combination spells success for residential water conditioning dealers. It brings together the features homeowners prefer with the timetested component designs professionals can trust for years of customer satisfaction.



EASY SERVICING

Cartridge-based seal and spacer design for quick and easy replacement.

FASTER SETUP TIME

10,000 RPM fast positioning motor with 12 volt DC drive.



EASY AND QUICK ASSEMBLY

A snap fit/clip system with a limited number of screw, allows an easier and quicker assembly and disassembly which facilitates the installation set-up and the maintenance.



OPTICAL TECHNOLOGY

Optical sensors control the backwash cycle for trustworthy, precise performance.

CLEAR BACKLIT DISPLAY

Easy visibility even in a dark basement.



SOFT WATER REFILL

Increases the regenration efficiency and helps reducing the system's maintenance.



CUSTOMIZE THE FRONT COVER / BEZEL

This option allows to create a unique identity.



3 INTERCHANGEABLE TIMERS

Allows professionals to upgrade a standard system in a premium one, simply by changing timer.

PLUG-AND-PLAY CONTROLLERS







MULTIPLE CONTROLLERS OPTION

Transform an ordinary system into a premium performer simply by changing controllers, thanks to the Pentair Fleck 5800 three interchangeable controller modules. All three modules attach to the valve with the same connector, making it easy to give homeowners a choice of timer features and functionality.

PROGRAM & PLAY

LXT - Storm*

Midsize LCD display comes preprogrammed for your choices of softener or filter and time clock or metered, with a maximum of 5 parameters to complete

*specifically for the 5800

COMPLETELY CUSTOMIZE-ABLE

SXT - Typhoon

Large LCD display and userselectable time clock or metered function; usable for filter or softener systems.

EXTREME DIY

XTR - Hurricane

Premium touch screen LCD display with two programmable relay outputs for both normally open and normally closed contacts.

XTR - HURRICANE

USER-FRIENDLY INTERFACE

- Detailed screen descriptions
- Color LCD display
- System error alarm shutoff
- Help/Assistance screen with optional dealer contact info
- Programmable Assistance Interval with alarm for service

ADVANCED FEATURES

- Proportional brining
- Chlorination/desinfection
- Continuous flow leak detection

EASY PROGRAMMING

- Master settings by category
- Familiar icons
- Intuitive navigation
- Password lock-out screen

FEATURES

5812 HIGH PERFORMANCE FLEXIBLE 1-1/4" VALVE

> 2.5" & 4" THREADED BASE



UPFLOW PLASTIC PISTON



DOWNFLOW PLASTIC PISTON

MECHANICAL STOPS

to prevent overtightening of plastic nuts

SEAL & SPACER "CLIPPING" CARTRIDGE WITH EPDM (BLACK) SEALS

for extended service life and simplified replacement



END CAP/PLUG

for an easy installation and removal using a screwdriver or hex wrench

5810 HIGH PERFORMANCE FLEXIBLE 1" VALVE

SIDE MOUNT METER

with encapsulated magnets for reduced maintenance



Chlorinator kit (for 5800 XTR)

Now available! Can be used on any 5800 XTR valve and installed in few minutes. The purpose of this chlorinator is to sterilize the resin hed

FLECK 5800 SERIES VALVES

NEW PERFORMANCES, NEW HEIGHTS

