

AUTOTROL® 762 TIMER

METERED CONTROL WITH FULLY PROGRAMMABLE CYCLE TIMES AND SALT AMOUNT



FEATURES/BENEFITS

- LCD display alternates between current flow rate and volume remaining
- Large LCD display for simplified programming
- Time of day super capacitor backup for power loss
- Queued regeneration is indicated by a flashing icon
- Easy installation with plug-in wiring harnesses
- Easy electronic programming
- Displays regeneration step and time remaining during regeneration
- Programming stored in memory and will not be lost due to power outages
- Adjustable Time of Regeneration

History

- Initial Setting Value
- Days since last regeneration
- Current Flow Rate
- Water used today since Time of Regeneration
- Water used since last regeneration
- Total water used since reset
- Average usage for each day of week
- Average service cycle
- Peak Flow Rate
- Day and Time of Peak Flow Rate
- Months since service
- Water used since last regeneration
- Number of regenerations since last serviced

OPTIONS

No salt detector indicates when to add salt *

Timer wall mount kits

Refill first for dry salt storage

* Not available on Magnum



UL recognized to the 979



Restriction of Hazardous Substance Compliant

WRSSKIN
WREKIN WATERSOFTNERS



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4003063 REV B MR14 © 2014 Pentair Residential Filtration, LLC. All Rights Reserved.