

Simplex Autotrol Water Softener

Resin Volume (litres)	Vessel Size inches	Service Flow m ³ /hr	capacity m ³ *	Salt used per regen. kg	Connections In / Out	Max Footprint		
						Width mm	Depth mm	Height mm
14	7 x 35	0.56	2.3	2.2	3/4"	525	378	1109
20	8 x 35	0.8	3.3	3.2	3/4"	550	378	1104
25	9 x 35	1	4	4	3/4"	577	378	1105
30	10 x 35	1.2	5	4.8	3/4"	599	378	1105
40	10 x 44	1.6	6.7	6.4	3/4"	719	440	1324
50	10 x 54	2	8.3	8	3/4"	719	440	1587
60	12 x 48	2.4	10	9.6	3/4"	765	440	1435
75	13 x 54	3	12.5	12	3/4"	1031	680	1584
100	14 x 65	4	16.7	16	1"	1059	680	1870
125	14 x 65	5	20	20	1"	1059	680	1870
150	16 x 65	5.7	25	24	1"	1176	760	1875
200	18 x 65	5.7	33	32	1"	1359	880	1997
250	21 x 60	10	41.6	40	2"	1442	880	1921
350	24 x 69	14	58	56	2"	1500	880	2171
500	30 x 72	16	83	80	2"	1810	1030	2341
700	36 x 72	16	116	112	2"	1967	1030	2441

*hardness @ 300 mg/l (calcium carbonate)

Wrekin