

Model Number	Capacity gal / liter	Maximum Operating Pressure psi / kPa / Bar	Drawdown 30/50 Setting** gal / liter	Diameter* inch / cm	Overall Height* inch / cm	Height* inlet/ outlet to floor inch / cm	System Connection	Assembly Weight* lb / kg	Pallet QTY.
WM-4 / WM0060 C	14.5 / 55	125 / 862 / 8.6	4.5 / 17.0	16 / 41	26 / 66	1 3/4 / 4.4	1" male NPT	14.5 / 6.6	9
WM-6 / WM0075 C	19.8 / 75	125 / 862 / 8.6	6.1 / 34.4	16 / 41	32 / 81	1 3/4 / 4.4	1" male NPT	17.75 / 8.1	9
WM-9 / WM0120 C	29.5 / 112	125 / 862 / 8.6	9.1 / 34.4	16 / 41	44 / 112	1 3/4 / 4.4	1" male NPT	24.75 / 11.2	9
WM-12 / WM0150 C	40.3 / 153	125 / 862 / 8.6	12.5 / 47.3	16 / 41	57 / 145	1 3/4 / 4.4	1" male NPT	65.7 / 29.8	9
WM-14WB / WM0180 C	47.1 / 178	125 / 862 / 8.6	14.6 / 55.3	21 / 53	41.3 / 105	2 1/4 / 5.7	1 1/4" male NPT	50 / 22.7	4
WM-20WB / WM0235 C	60.0 / 227	125 / 862 / 8.6	18.5 / 70.0	24 / 61	41.5 / 105	2 1/4 / 5.7	1 1/4" male NPT	72.75 / 33.0	4
WM-23 / WM0300 C	79.6 / 301	125 / 862 / 8.6	24.6 / 93.1	21 / 53	62 / 157	2 1/4 / 5.7	1 1/4" male NPT	43 / 19.5	4
WM-25WB / WM0330 C	86.7 / 328	125 / 862 / 8.6	26.8 / 101.5	24 / 61	55 1/4 / 140	2 1/4 / 5.7	1 1/4" male NPT	72.75 / 33.0	4
WM-35WB / WM0450 C	119.7 / 453	125 / 862 / 8.6	37.0 / 140.1	24 / 61	74 1/4 / 189	2 1/4 / 5.7	1 1/4" male NPT	102 / 46.4	N/A



Durable interior air cell is fully replaceable and constructed of heavy-gauge engineered polymer.

One piece, seamless inner shell molded of premium, high-density polyethylene.

Outer shell is a composite of continuous fiberglass strands sealed with high-grade epoxy resin.

Sturdy, molded polymeric base is corrosion and impact proof.

Bottom inlet/outlet one-piece drain is custom molded of high-impact PVC.